

HTTP Status	
Informative	
100	Continue
101	Switching Protocol
Success	
200	OK
201	Created (POST)
202	Accepted
203	Non-Authoritative Information
204	No Content
Redirect	
301	Move Permanently
Client Error	
400	Bad Request
401	Unauthorized
402	Payment Required
403	Forbidden
404	Not Found
408	Timeout
429	Too Many Requests
451	Illegal
Server Error	
500	Internal Server Error
502	Bad Gateway
503	Service Unavailable

Python	
List	
lst	[10, 20, 30, 40, 50]
lst[-1]	[10, 20, 30, 40]
lst[1:-1]	[20, 30, 40]
lst[:2]	[10, 30, 50]
lst[::-1]	[50, 40, 30, 20, 10]
and, or, not, True False	
Import	
from mod import mod1, mod2	mod1()
import mod	mod.mod1()
Operators	
+ - // % *	
Operations	
a	
.len()	
.sorted(list)	
list.sort()	
.reversed(list)	
list.reverse()	
Lists Operations	
.append()	[, , []]
.extend()	[, , ,]
.insert(index, value)	
.remove()	
Dictionaries Operations	
{key: value}	
d[key]	value
.update()	

Python (cont)	
.values()	
.keys()	
a	
Strings	
.count()	
.index()	
.upper()	
.capitalize()	
.split(" ")	
.strip(" ")	Remove todos os caracteres
MySQL	
SELECT column1, column2 FROM table_name WHERE x = "ads" ORDER BY column1 DESC	
SELECT COUNT(column_name) FROM table_name WHERE condition;	
SELECT AVG(column_name) FROM table_name WHERE condition;	
SELECT SUM(column_name) FROM table_name WHERE condition;	
SELECT column1, ... FROM table_name WHERE columnN LIKE pattern; % - any, _something	
INSERT INTO table name (column1, column2, column3, ...) VALUES (value1, value2, value3, ...)	
UPDATE table_name SET column1 = value1, column2 = value2, ... WHERE condition	
DELETE FROM table_name WHERE condition	



MySQL (cont)

CREATE TABLE table_name (column1 datatype, column2 datatype, ...)

DROP TABLE table_name

DROP DATABASE databasename

ALTER TABLE table_name ADD column_name datatype;

ALTER TABLE table_name DROP COLUMN column_name;

ALTER TABLE table_name MODIFY COLUMN column_name datatype;

Java

Arrays

.equals(Object[] arr1, Object[] arr2)

.sort(Object[] arr)

.toString()

String

.indexOf(char a)

.charAt(int index)

.equals(String s)

.format(String s, int 1, String 2, int 3, ...)

.length()

.substring(int beginIndex, int endIndex)

.toLowerCase()

.toUpperCase()

List<E>

.add(int index, E element)

.add (E element)

.contains(Object o)

.get(int index)

.indexOf(Object o)

Java (cont)

.isEmpty()

.remove(int index)

.remove(Object o)

.set(int index, E Element)

.size()

.toArray()

.subList(int fromIndex, int toIndex)

HashMap<Object Key, Object Value>

.get(Object Key)

.put(Key key, Value value)

.remove(Object key)

.replace(K key, V value)

.size()

.values()

.containsKey(Object Key)

.containsValue(Object Value)

HashSet<E>

.add(E e)

.contains(Object o)

.remove(Object o)

.size()

.isEmpty()

.clear()

jUnits

void teste(){ ... } assertEquals(exp, comp)

GIT

Criar repo git init

Aceder a staging area git status

Adicionar ficheiro a Staging Area git add {nome do ficheiro}

Remover da Staging Area git reset HEAD -- <file>

Dar commit git commit -m "- Commit message"

Criar novo branch git branch <new-branch-name>

Mudar de branch git checkout {branch}

Merge Branch git merge <branch-name>

Push para remoto git push <remote> <branch>

Atualizar git pull

Remover ficheiro do repositório git rm <file>

Mongoose

Schema.create({ nome: name, password })

Schema.findOne({ _id: id })

Schema.find({ name: name })

Schema.exists({ _id: id })

Schema.updateMany({ _id: id }, {name: name })

Schema.deleteOne({ _id: id })



By Afonso Benedito

cheatography.com/afonso-benedito/

Published 19th June, 2022.

Last updated 20th June, 2022.

Page 2 of 3.

Sponsored by **ApolloPad.com**

Everyone has a novel in them. Finish Yours!

<https://apollopadd.com>

SOLID Principles

Single Responsibility	Class can have one responsibility
Open/Closed	Interfaces = - if's
Liskov Substitution	Subclass can do what Super does
Interface Segregation	Threedimensional shape x shape
Dependency Inversion	

ExpressJS

```
const express = require('express')();
```

```
Get      app.get('/info', (req, res)=>{})
```

```
Post     app.post('/:id', (req, res) => {})
```

```
Send     res.status(200).send({})
```

```
Redirect  res.redirect(301, '/')
```

ReactJs

```
render(){return(<div>...</div>)}
```

```
Array => .map(() => { ... })
```

```
onClick = {() => this.handleSomething()}
```

```
Counters: <Counter      Counter: this.props.  
onDelete={}/>           onDelete
```

Class

```
state = {...json...}
```

```
this.setState({count: this.state.count + 1})
```

```
componentDidMount
```

```
componentDidUpdate
```

```
componentWillUnmount
```



By Afonso Benedito

cheatography.com/afonso-benedito/

Published 19th June, 2022.

Last updated 20th June, 2022.

Page 3 of 3.

Sponsored by **ApolloPad.com**

Everyone has a novel in them. Finish Yours!

<https://apollopad.com>