

Command Line Tools

<code>meteor --help</code>	Prints the help information for the meteor command
<code>meteor create <app_name></code>	Creates a new Application called <app_name>
<code>meteor</code>	Starts your application
<code>meteor mongo</code>	Connects to the running app's MongoDB instance
<code>meteor add <package></code>	Adds a new package to the application
<code>meteor reset</code>	Resets the project state (removes the local DB!)

Core

<code>Meteor.isClient</code>	Value is true in client environment	Anywhere
<code>Meteor.isServer</code>	Value is true in server environment	Anywhere
<code>Meteor.isCordova</code>	Value is true in a Cordova mobile environment	Anywhere
<code>Meteor.startup(func)</code>	Run the function when the client/server starts	Anywhere
<code>Meteor.absoluteUrl([path], [options])</code>	Generates an absolute URL pointing to the application	Anywhere

Folders

<code>/.meteor</code>	Holds the meteor-specific files
<code>/client</code>	Files only visible/executed on the Client
<code>/client/compatibility</code>	For JavaScript files that rely on variables declared with var at the top level. These scripts are executed without being wrapped in a new variable scope.
<code>/server</code>	Files only visible/executed on the Server
<code>/public</code>	Files served as-is to the Client
<code>/private</code>	Files are only accessible from the Server code
<code>/tests</code>	Used for local tests only. Any files in this folder is not loaded anywhere in the running applications.