

Select Statement

Select Statements

show the whole table

Select * from <TableName>

Select * from Sales.salesperson;

Returns the total number of rows that match our search.

Select count (*) From Person.Person;

Top 10

Select top 10 * From Person.Address

bottom 10

Select top 10 * From person.Address
order by AddressID desc

Select Statement

Aggregate Functions

SUM

Select sum(TotalDue) From Sales.SalesOrderHeader;

AVERAGE

select avg(TotalDue) from Sales.SalesOrderHeader;

Largest Value

select max(TotalDue) from Sales.SalesOrderHeader;

Smallest Value

select min(TotalDue) from Sales.SalesOrderHeader;

Select Statement

other tips

Multiple values displayed

select Count(TotalDue) as NumOfOrders
,min(TotalDue) as [Min], max(TotalDue) as [Max],
sum(TotalDue) as [TOTAL], AVG(TotalDue) as Average
from Sales.SalesOrderHeader
Where PurchaseOrderNumber is not Null;

Distinct

Distinct Clause

Select Distinct [Name], CurrencyCode from
sales.ss_currency
select * from sales.ss_currency

Joins

Inner Joins - (intersecting data)

INNER JOINS

Select sod.productID as [Product], soh.SalesOrderNumber as [OrderNumber],
soh.CustomerID as [Customer], SOH.TotalDue as [TOTAL]
from sales.SalesOrderDetail SOD
inner join Sales.SalesOrderHeader SOH
on SOD.SalesOrderID = SOH.SalesOrderID;

Joins

Left Joins

LEFT Join

Select PP.BusinessEntityID, PP.FirstName as [FirstName],
PP.LastName as [Surname], PPH.PhoneNumber as [PhoneNumber]
from Person.Person PP
left join Person.PersonPhone PPH
on PP.BusinessEntityID = PPH.BusinessEntityID
where PPH.BusinessEntityID is NULL;

Joins

Left Outer Join

LEFT Outer Join

Select PP.BusinessEntityID, PP.FirstName as [FirstName],
PP.LastName as [Surname], PPH.PhoneNumber as [PhoneNumber]
from Person.Person PP
left outer join Person.PersonPhone PPH
on PP.BusinessEntityID = PPH.BusinessEntityID
order by pp.BusinessEntityID

Having Clause

select CurrencyCode, Name from sales.ss_currency
group by CurrencyCode, Name
having count (*)>1

Acending / Decending

Order BY Decending

Update

Update multiple columns

select * from sales.SS_Currency
Update sales.SS_Currency
Set Name = 'Shilpa Dollar'
Where CurrencyCode = 'SHD'
or currencyCode ='BKS';
select * from sales.SS_Currency
Where CurrencyCode = 'SHD'
or currencyCode ='BKS';

Change Tables

COPY TABLE

Select * into new_table from old_table
Select * into sales.SS_Currency from
sales.Currency

DROP - delete contents of table

drop table sales.SS_salesperson_Own

Tables

Create Table

Create Table sales.SS_salesperson_Own
(SalesPersonID int not NULL Identity,
SalesPersonName varchar(100) not Null,
ModifiedDate datetime,
Notes varchar(max),
IsManager bit,
commission decimal(10,2))

Changing Data

Update / Delete / Insert

UPDATE

update sales.SS_Currency set [Name] =
'SS dollar', ModifiedDate = GETDATE()
where CurrencyCode = 'SSD';
select * from sales.SS_Currency
where CurrencyCode = 'SSD';

DELETE

Delete from sales.SS_Currency
where CurrencyCode = 'SSD';
select * from sales.SS_Currency
where CurrencyCode = 'SSD';

INSERT INTO

Insert Into sales.SS_Currency (CurrencyCode,
[Name], ModifiedDate)
Values ('SSD','ShilpaDollar', GETDATE())

Date and time

Date and time

```
select GETDATE();
```

extract Date

```
Select FORMAT(GETDATE(),'dd/MM/yyyy')
```

extract time

```
select FORMAT(GETDATE(),'hh:mm:ss')
```

```
select * from sales.SpecialOffer
where format(StartDate, 'dd/MM/yyyy') =
'31/05/2011'
order by DiscountPct desc
```

set Database to be used

USE

```
use AdventureWorks2019
```

```
Select * From Sales.SalesReason
Order by [name] desc;
```

Order BY Acending

```
Select * From Sales.SalesReason
Order By [name];
```

Update

Update Multiple Rows

Update multiple rows

```
Update sales.SS_Currency
Set CurrencyCode = 'SHI' , [Name] = 'Shi
Dollar'
Where CurrencyCode = 'SHD';
select * from sales.SS_Currency
Where CurrencyCode = 'SHI'
or currencyCode ='BKS';
```

Insert

Another Example of - Insert Into

```
insert into sales.SS_salesperson_Own (
SalesPersonName, ModifiedDate , Notes ,
IsManager, commission)
values
( 'James Smith', GETDATE(), 'likes to sing',
0, 456.55),
( 'carrol james', GETDATE(), 'likes to
dance', 0, 556.55),
( 'Aarav Prasad', GETDATE(), 'likes to play
guitar', 0, 1000.00),
( 'Aanya Prasad', GETDATE(), 'likes to play
Cello', 0, 1000),
( 'KPBS', GETDATE(), 'likes chips', 0,
5943.24),
( 'SS', GETDATE(), 'likes to play Cello', 0,
1000000)
```



By **Shilpa** (freesprited)
cheatography.com/freesprited/

Published 13th August, 2026.
Last updated 28th August, 2022.
Page 1 of 2.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>