

Declaration

```
explicit <?php
location $print er[0] = " Las erjet 2001 $pr int er[ 'R&B
";
PRINTERS'] = " Las erjet 2002";
$print er[1] = " LMP 172 4fa st $pr int er[ 'Ja ckson
";
Printers'] = " J20 01L ase rje -
t";
implicit <?php
location $printer[] = " Las erjet 2001"; pri nt_ r($ pri nter);

$printer[] = " LMP 172 4fa st"; //r esult
array (
    'R&B
PRINTERS' => " Las erjet 2002",
    'Ja -
ckson Printers' => " J20 01L -
ase rje t",
)
```

Associative Arrays

```
<?php
location $printer[] = " Las erjet 2001"; pri nt_ r($ pri nter);

$printer[] = " LMP 172 4fa st"; //r esult
array (
    'R&B
PRINTERS' => " Las erjet 2002",
    'Ja -
ckson Printers' => " J20 01L -
ase rje t",
)
```

with **associative arrays**, you can reference the items in an array by name rather than by number.

The for..each as loop

```
<?php
$paper = array( " Cop ier ",
" Ink jet ", " Las er", " Pho -
to");
$j = 0;
for eac h($ paper as $item)
{
echo "$j: $item< br> ";
++$j;
}
?>
```

Functions

Functions

is_array()

```
echo (is_ar ray ($p rod ucts)) ? "
y";
```

count()

```
echo count( $pr odu cts);
```

sort()

```
sort($products);
sort($products, SORT_NUMERIC);
sort($products, SORT_S TRING);
```

shuffle()

```
shuffl e($ cards);
```

explode()

```
<?php
$temp = explode(' ', "This is a se
print_ r($ temp);
?>
```

extract()

```
extrac t($ _GET);
```

compact()

```
<?php
$planet = " Gal lif rey ";
$system = " Gri dlo ck";
$const ell ation = " Kas ter -
bor ous ";
$contact = compact 'planet',
'system', 'const ell ati on';
```

use compact, the inverse of extract, to create an array from variables and their values.

Multidimensional Arrays

```
<?php
$pr oducts = array(
    'pens' => array(
        'ball' =>
"Ball Point",
        'hi lite' =>
" Hig hli ght ers ",
        'ma rker' =>
" Mar ker s"),
    'misc' => array(
        'tape' => " -
Sticky Tape",
        'glue' => " -
Adh esi ves ",
        'clips' => " -
Pap erc lip s"
    )
);
```

Assignment using the array Keyword

```
`<?php
$p1 = array("China", "Russia",
"Austria", "Turkey");
$p2 = array
(
'china' => "Beijing",
'Russia' => "Moscow" ,
'Austria' => "Vienna",
'Turkey' => "Ankara"
);
```



By **shirM**
cheatography.com/shirM/

Published 7th May, 2023.
Last updated 7th May, 2023.
Page 1 of 2.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>