

Datatypes

int	2, 5, -3, -10, 22
float	2.5, 3.2, 10.15, -2010, 0, 0.01
String	"Nom", "Client", "ModDePasse", "-5.2"
boolean	true, false

Declarations

DATATYPE VARIABLE;

DATATYPE VARIABLE = VALEUR;

DATATYPE VARIABLE, VARIABLE2;

DATATYPE VARIABLE = VALEUR,
VARIABLE2 = VALEUR2;

Conditional

if if(CONDITION) {}

if else if(CONDITION) {} else {}

if else if(CONDITION) {} else if(CONDITION2) {}

Printing

System.out.println("Message");

System.out.println(Variable);

Scanning

import java.util.Scanner; Scanner NOM = new
Scanner(System.in);

int variable = scanner.nextInt();
float variable = scanner.nextFloat();

String variable = scanner.nextLine();

Boucle

while while(CONDITION) {}

for for(int i = 0; i < max; i++) {}

do while do {} while(CONDITION);

Arrays (Tableau)

TYPE nom[]; nom = new TYPE[TAILLE];

TYPE nom[] = new TYPE[TAILLE];
TYPE nom = {
valeur1, valeur2,
valeur3};

Array Loop

```
int tableau[] = new int[5];
for(int i = 0; i < 5; i++){
    tableau[i] = valeur;
    // possible:
    tableau[i] = scanner.nextInt();
}
```



By **Spounka Von Schpeiner**
(spounka)
cheatography.com/spounka/

Published 21st September, 2022.
Last updated 21st September, 2022.
Page 1 of 1.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>